

IPitomy IP330 HD SIP Phone

Gigabit Ethernet

Designed for Business

The IPitomy IP330 includes outstanding business features and flexibility in an enterprise grade IP telephone. Designed for business applications, this multi-line SIP telephone delivers the advanced features and performance expected in most business environments.. Featuring a 128 x64 graphic dot matrix LCD screen display, the IP330 supports 3 lines with call appearances, has 4 multi function Soft Keys and 8 programmable feature buttons that support popular features like Park, Busy Lamp and Speed Dial.

The IP330 is an Enterprise grade endpoint with features that support typical business operations plus High Definition Audio supporting the G.722 codec. Shown with optional IPX32 expansion module.



Features

- 128 x64 graphic dot matrix display, 5 lines visible (including one line icon display)
- High-fidelity sound quality: HD encoding
- 3 SIP accounts
- 12 programmable keys
- Up to 6 - 32 Button Expansion Modules
- 2 100BASE-T Ethernet interfaces, support POE
- Adjustable Stand
- Integrated Wall Mount
- Volume control
- IP direct dial
- Custom ring tone
- Phonebook
- Call records:
 - Dialed calls
 - Received calls
 - Missed calls
- Friendly user interface
- One key Clear menu (button c)
- One key to view version number and network state (button c)
- Hardware diagnostics
- Multi-Language
- Programmable keys
- 3 configuration models: web page, phone and IPitomy PBX auto provision
- Load default setting, capture package and system log export

Detail

- 3 SIP accounts (with dual color LED)
- 49 buttons (includes 8 programmable keys)
- 3 Party Conference
- Voicemail
- Busy Lamp Support
- Call waiting tone
- Multi-Language display
- Supports IPitomy Auto Provisioning TFTP/HTTP
- Automatic firmware updates
- Support TLS/HTTPS encryption protocol
- Power Over Ethernet (POE)
- RJ-9 headset interface
- Dual network interface
- Support 6 Expansion Units up to 192 programmable keys for attendant console
- Support VPN, VLAN QOS(802.1pq)
- LLDP
- Support TLS(Transport Layer Security)
- Support HTTPS(client)
- Support TLS(Transport Layer Security)
- Support information authentication mechanism MD5
- Support AES encryption protocol
- Support phone locks,

Phone Features

- Support 3 SIP accounts
- Hotline
- Hold
- Call waiting
- Call transfer (blind,attended)
- Caller id
- Redial
- Mute
- DND/Pause
- Auto answer
- 3 Party Conference
- Speed-dial
- Voicemail Message Indicator
- Message lamp

Advanced Features

- Enterprise phonebook
- LDAP phonebook
- Fuzzy search
- Customizable home screen
- IPitomy Provisioning
- Intercom, paging
- BLF

Audio Features

- Wideband encoding: G.722
- Narrow band encoding: G. 711.μ/A, G.723.1, G.729AB
- Support VAD, CNG, AEC, PLC, AJS, AGC, such as audio processing ribbon coding
- Full duplex speaker, with automatic echo elimination (AEC)

Network Features

- (2) 10/100/1000 Ethernet Interface
- Support SIP v1(RFC2543), v2(RFC3261)
- Support DNS-SRV RFC3263
- Support STUN
- 3 DTMF modes: In-band, RFC2833, SIP INFO
- Network :static, DHCP, PPPOE
- Support bridge and router model
- Support TFTP/DHCP/PPPOE terminal
- Support DNS client, built-in NAT/DHCP service
- Login, logout in the web page

Configuration Manager

- TFTP/HTTP automatic configuration

Physical Properties

- 128 x64 graphic dot matrix display, 5 lines visible (including one line display icon)
- 49 buttons(includes 8 programmable keys)
- One RJ-9(4P4C) handset interface
- Two 1000 BASE-T Ethernet interfaces
- One RJ-45 Expansion interface
- The power adapter: AC 100-240V input, DC 5V/1A output
- Support POE power supply (IEEE 802.3af)
- Power: 6w
- Net weight: 1.2KG
- Bare machine size: 11.3"X8.43"X3.54"
- Operating environment humidity: 10-90%
- Working environment temperature: 0~60℃

IPitomy Communications, LLC
1940 Northgate Blvd. B1
Sarasota, FL 34234

IPITOMY